

GUARDRAIL DELINEATOR “FLAT MOUNT”

SHUR-TITE® Guardrail Flat Mount Specification

- 1] The Shur-Tite® Guardrail Flat Mount is a field-proven, impact-resistant delineator manufactured from recycled composite materials.
- 2] The posts are 19” or 33” in height and manufactured utilizing a minimum of 70% recycle material.
- 3] The post features a durable exterior with an integrated premium UV inhibitor package to resist degradation from prolonged sun exposure.
- 4] The exterior finish is smooth to resist road grime and mildew while maintaining high visibility in low-light and adverse weather conditions.
- 5] The top of the post is permanently sealed and partially flattened, transitioning to a round profile to provide structural integrity and 360-degree visibility.
- 6] The delineator is designed to withstand impacts from snow plow windrows and typical roadway conditions.
- 7] The flattened top sections accommodates up to a 3” x 12” reflective sheeting on both sides of the post.
- 8] The flat mount is supplied with either (2) #14 x 1-1/2” self-tapping screws for steel guardrail posts, or (2) #14 x 2-1/2” lag screws for timber or composite guardrail posts or blocks.
- 9] Shur-Tite® Products provides a factory representative for initial installation training to assist DOT personnel or contractors and ensure compliance with state standards and manufacturer recommendations.



1920 North Weaver
Gainesville, TX 76240



512.218.9500



sales@shur-tite.com
www.shur-tite.com